



SUBMITTAL SHEET

JOB NAME		ITEM TAG	
JOB LOCATION		PART NUMBER	
CONTRACTOR	DATE		
ENGINEER APPROVAL	DATE		

LEAD-FREE QUARTER-TURN SILLCOCK

R-673NL and R-674NL

Lead-free design is suitable for all no-lead potable water installations, in full compliance of all lead-free plumbing laws.

Quarter-turn, bubble-tight positive shutoff.

Forged brass construction eliminates casting-related leaks.

More durable than traditional stop-type valves.

Compact design is ideal for confined applications.

Superior flow characteristics.

All 3/4" GHT (garden hose) outlets accept 3/4" hose-thread-mounted vacuum breakers*, including our Models T-553NL, T-553CNL, T-554, T-555, T-556, T-557 and T-557C.

Available in nominal 1/2" and 3/4" FNPT or CTS inlet x 3/4" MGHT outlet sizes

*These vacuum breaker models are not included with the valves and do not appear on this submittal sheet. Please check your local backflow prevention code requirements and contact Legend for additional submittal information.

Working Pressure, Non Shock (PSI)

Cold working pressure (CWP): 200 p.s.i.

Saturated steam (WSP): Not suitable for steam service

- Third-party tested and certified in compliance with U.S. Federal Public Law 111-380 (National lead-free plumbing law).
- NSF certified to ANSI / NSF Standard 61 Annex G. Meets NSF 372 lead content requirements.
- CSA certified for Canadian plumbing applications.
- End connections comply with the following specifications:

ANSI / ASME B1.20.1 (FNPT)

ANSI / ASME B16.18 (CTS)

ASME B1.20.7 (Male garden hose)

Manufactured in an ISO accredited facility





MATERIAL SPECIFICATION PART MATERIAL **SPECIFICATION** Lead-free forged brass CW 510L UNS C28500 Body 2 Polyamide PA6 Nylon* Downstream seat CW 510L UNS C28500 Seat retainer Lead-free forged brass PTFE Upstream seat Teflon* 5 CW 510L UNS C28500 Lead-free forged brass Ball CW 510L UNS C28500 Stem Lead-free forged brass Stem o-ring EPDM rubber Commercial grade Anti-friction washer Acetal resin POM, Commercial grade Handle Aluminum Commercial grade 10 Handle fastener Carbon Steel Commercial grade, galvanized

^{*}Teflon and Nylon are registered trademarks of DuPont.

DIMENSI	ONS		
Size	Α	В	С
R-673NL	(FNPT)		
1/2"	2.88	2.00	2.33
3/4"	2.88	2.00	2.33
R-674NL	(CTS)		
1/2"	2.88	2.00	2.88
3/4"	2.88	2.00	2.75

